

SELECTION & SPECIFICATION DATA

Type	Asphalt Cutback
Description	Blackhawk 5114 Low-VOC Asphalt Primer is a low VOC cutback asphalt primer that imparts a tacky surface to porous roof substrates. It is used to prime concrete, wood, and metal substrates for asphalt-based roofing adhesives, hot melts, and self-adhered membranes.
Uses	<ul style="list-style-type: none"> • Primer for asphaltic adhesives • Hot-melt asphaltic membranes
Color	Black
Topcoats	Consult ErgonArmor
Finish	Matte
Dry Film Thickness (DFT)	5 – 15 mils
Solids Content	64% by weight
VOC Value(s)	<350 g/L (2.92 lbs/gal)

SUBSTRATES & SURFACE PREPARATION

All	Surfaces must be clean and dry. Remove all dirt, dust, oil and other contaminants.
Previously Painted Surfaces	Consult with ErgonArmor Technical Service.

SAFETY

Safety	Mixes and applications of this product present a number of hazards. Read and follow the hazard information, precautions and first aid directions on the individual product labels and safety data sheets before using.
---------------	--

Ventilation	Use in well ventilated areas
--------------------	------------------------------

MIXING AND THINNING

Mixing	Light mixing may be necessary. Ready to use if sealed properly in ideal storage conditions.
Thinning	Not recommended
Cleanup	Mineral spirits or similar solvent

APPLICATION GUIDANCE

Airless Spray	Pump size: 15:1 or greater Spray hose: 200 ft maximum x 1/2-inch ID Whip length: 15 ft x 1/4-inch ID
Brush	Wide, fiber brush
Roller	Low-nap phenolic core roller

PACKAGING, ESTIMATING & HANDLING

ITEM #	PACKAGING
K-5114-053-001	Drum - 53 gallons
K-5114-275-001	Tote - 270 gallons
Theoretical Coverage Rate	1050 square feet per gallon at 1 mil DFT
Storage & Shelf Life	Estimated shelf life is 12 months when stored in a dry area at 75°F (24°C). Actual shelf life may vary with storage conditions. Do not store below 40°F (4°C) or above 110°F (43°C). Store indoors. Always inspect the product prior to use to ensure uniform consistency.

Rev 12/21

TERMS AND CONDITIONS OF SALE

While statements, technical information and recommendations contained herein are based on information our company believes to be reliable, nothing contained herein shall constitute any warranty, express or implied, with respect to the products and/or services described herein and any such warranties are expressly disclaimed. We recommend that the prospective purchaser or user independently determine the suitability of our product(s) for their intended use. No statement, information or recommendation with respect to our products, whether contained herein or otherwise communicated, shall be legally binding upon us unless expressly set forth in a written agreement between us and the purchaser/user. For all Terms and Conditions of Sale see ergonarmor.com.