# SAFETY DATA SHEET



### 1. Identification

**Product identifier** FLEXJOINT™ U500 SEALANT PART A RESIN

Other means of identification None.

Recommended use Not available. **Recommended restrictions** None known.

Manufacturer/Importer/Supplier/Distributor information

**Company Name** ErgonArmor, a division of Ergon Asphalt & Emulsions, Inc.

**Address** 2829 Lakeland Drive

Jackson, MS 39232

1-800-222-7122

1-877-982-7667

**USA** 

After hours telephone

number

**Normal work hours** 

Website

telephone number

www.ergonarmor.com E-mail sds@ergon.com

**Emergency 24-hour** 

telephone number **Information on** operation hours

CHEMTREC: North America 1-800-424-9300 International 1-800-527-3887

8:00 a.m. to 5:00 p.m.

# 2. Hazard(s) identification

**Physical hazards** Not classified.

**Health hazards** Category 4 Acute toxicity, oral

> Serious eye damage/eye irritation Category 2 Sensitization, skin Category 1 Category 1

**Environmental hazards** Hazardous to the aquatic environment,

acute hazard

Hazardous to the aquatic environment, Category 1

long-term hazard

**OSHA** defined hazards Not classified.

**Label elements** 



Signal word Warning

**Hazard statement** Harmful if swallowed. Causes serious eye irritation. May cause an allergic skin reaction. Very

toxic to aquatic life. Very toxic to aquatic life with long lasting effects.

**Precautionary statement** 

Avoid breathing dust/fume/gas/mist/vapors/spray. Wash hands thoroughly after handling. Do **Prevention** 

not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wear protective

gloves/protective clothing/eye protection/face protection.

IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical Response

advice/attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell. Rinse mouth. Specific treatment see Section 4 of this SDS. Wash contaminated

clothing before reuse. Collect spillage.

Material name: FLEXJOINT™ U500 SEALANT PART A RESIN

1/7 7853 Version #: 01 Issue date: 02-17-2025

**Storage** Store away from incompatible materials.

**Disposal** Dispose of contents/container in accordance with local/regional/national/international

regulations.

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information

None.

## 3. Composition/information on ingredients

#### **Mixtures**

Chemical name	Common name and synonyms	CAS number	%
DIETHYLTOULENEDIAMINE		68479-98-1	5 - 15
TETRAHYDROXYPROPYLETHYLEN EDIAMINE		102-60-3	5 - 10
Other components below reportable	e levels		82.5

#### 4. First-aid measures

**Inhalation** Move to fresh air. Oxygen or artificial respiration if needed. Call a physician if symptoms develop

or persist.

**Skin contact** Wash the skin immediately with soap and water. Immediately take off all contaminated clothing.

Wash contaminated clothing before reuse. Get medical attention if irritation develops and

persists.

**Eye contact** Immediately flush eyes with plenty of water for at least 15 minutes. Continue rinsing. Remove

contact lenses, if present and easy to do. Get medical attention if irritation develops and

persists.

**Ingestion** Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach

content doesn't get into the lungs. Never give anything by mouth to a victim who is

unconscious or is having convulsions. Call a POISON CENTER or doctor/physician.

Most important

symptoms/effects, acute and delayed

and delayed

Direct contact with eyes may cause temporary irritation. Exposure may cause temporary irritation, redness, or discomfort. Skin irritation. Irritating to mouth, throat, and stomach. May cause respiratory irritation. May cause allergic respiratory reaction.

Indication of immediate medical attention and special treatment needed

Treat symptomatically.

**General information** Ensure that medical personnel are aware of the material(s) involved, and take precautions to

protect themselves.

#### 5. Fire-fighting measures

**Suitable extinguishing media** Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

**Unsuitable extinguishing** 

media

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from

the chemical

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for

and precautions firefighters

**Special protective equipment** Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting

equipment/instructions

Move containers from fire area if you can do so without risk.

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials.

**General fire hazards** 

No unusual fire or explosion hazards noted.

#### 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Do not touch or walk through spilled material. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Avoid breathing mist or vapor. Ensure adequate ventilation. Wear appropriate personal protective equipment. For personal protection, see section 8 of the SDS.

Material name: FLEXJOINT™ U500 SEALANT PART A RESIN

7853 Version #: 01 Issue date: 02-17-2025

Methods and materials for containment and cleaning up

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the

SDS.

**Environmental precautions** Avoid discharge into drains, water courses or onto the ground.

## 7. Handling and storage

**Precautions for safe handling** (

Observe good industrial hygiene practices. Wear suitable protective clothing, gloves and eye/face protection. Protect from moisture. Avoid contact with eyes, skin, and clothing. Provide adequate ventilation. Wash hands thoroughly after handling. Use care in handling/storage.

Conditions for safe storage, including any incompatibilities

Store in tightly closed container. Store in cool, dry place in tightly closed receptacles (60-80°F recommended). Keep container in a well-ventilated place. Keep away from heat and flame. Keep under nitrogen.

## 8. Exposure controls/personal protection

Occupational exposure limits

This mixture has no ingredients that have PEL, TLV, or other recommended exposure limit.

Biological limit values

No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

Provide adequate ventilation, including appropriate local extraction, to ensure that the defined

occupational exposure limit is not exceeded.

## Individual protection measures, such as personal protective equipment

**Eye/face protection** Wear safety glasses with side shields (or goggles).

**Skin protection** 

**Hand protection** Chemical resistant gloves are recommended. If contact with forearms is likely wear gauntlet

style gloves. Impervious gloves. Neoprene. Rubber, neoprene or PVC. Nitrile.

**Other** Wear suitable protective clothing.

**Respiratory protection** When workers are facing concentrations above the exposure limit they must use appropriate

certified respirators.

**Thermal hazards** Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Keep away from foodstuffs, beverages and feed.

## 9. Physical and chemical properties

Appearance Liquid.
Physical state Liquid.

Form Liquid.
Color Cloudy.

Odor Amine-like.
Odor threshold Not available.
PH Not available.
Melting point/freezing point Not available.

Initial boiling point and

boiling range

>392 °F (>200 °C)

Flash point >302.0 °F (>150.0 °C)

Evaporation rate Not available.

Flammability (solid, gas) Not applicable.

Upper/lower flammability or explosive limits

**Explosive limit - lower** 

Not available.

(%)

**Explosive limit - upper** Not available.

(%)

Material name: FLEXJOINT™ U500 SEALANT PART A RESIN 7853 Version #: 01 Issue date: 02-17-2025

Vapor pressureNot available.Vapor densityNot available.Relative density1.03 g/cm3

Solubility(ies)

Solubility (water) Not available.

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperatureNot available.Decomposition temperatureNot available.Viscosity1000 - 3000 cP

Other information

**Explosive properties** Not explosive. **Oxidizing properties** Not oxidizing.

### 10. Stability and reactivity

**Reactivity**The product is stable and non-reactive under normal conditions of use, storage and transport.

**Chemical stability** Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

**Conditions to avoid** Exposure to moisture. Heat.

**Incompatible materials** Strong acids. Oxidizing agents. Bases.

**Hazardous decomposition** 

products

Nitrogen oxides (NOx). Carbon monoxide. Carbon dioxide. Sulfur oxides.

## 11. Toxicological information

Information on likely routes of exposure

**Inhalation** Prolonged inhalation may be harmful.

**Skin contact** May cause an allergic skin reaction. Prolonged skin contact may cause temporary irritation.

**Eye contact** Causes serious eye irritation.

**Ingestion** Harmful if swallowed.

Symptoms related to the physical, chemical and toxicological characteristics

Direct contact with eyes may cause temporary irritation. Exposure may cause temporary irritation, redness, or discomfort. May cause respiratory irritation. Irritating to mouth, throat,

and stomach. May cause an allergic skin reaction. Skin irritation.

Information on toxicological effects

**Acute toxicity** Harmful if swallowed.

**Skin corrosion/irritation** Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye

irritation

Causes serious eye irritation.

Respiratory or skin sensitization

**Respiratory sensitization** Not a respiratory sensitizer.

**Skin sensitization** May cause an allergic skin reaction. Prolonged skin contact may cause temporary irritation. **Germ cell mutagenicity** No data available to indicate product or any components present at greater than 0.1% are

No data available to indicate product of any components present at greater than 0.1% a

mutagenic or genotoxic.

**Carcinogenicity** Not classifiable as to carcinogenicity to humans.

IARC Monographs. Overall Evaluation of Carcinogenicity

Not listed.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

**US. National Toxicology Program (NTP) Report on Carcinogens** 

Not listed.

**Reproductive toxicity**This product is not expected to cause reproductive or developmental effects.

**Specific target organ toxicity** Not classified.

- single exposure

Material name: FLEXJOINT™ U500 SEALANT PART A RESIN
7853 Version #: 01 Issue date: 02-17-2025

Specific target organ toxicity

repeated exposure

Not classified.

**Aspiration hazard** 

Not an aspiration hazard.

## 12. Ecological information

**Ecotoxicity** Very toxic to aquatic life with long lasting effects.

Persistence and degradability No data is available on the degradability of any ingredients in the mixture.

**Bioaccumulative potential** No data available. Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

### 13. Disposal considerations

**Disposal instructions** Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of

contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the

waste disposal company.

Waste from residues /

unused products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner.

Since emptied containers may retain product residue, follow label warnings even after container Contaminated packaging

is emptied. Empty containers should be taken to an approved waste handling site for recycling

or disposal.

## 14. Transport information

DOT

Not regulated as dangerous goods.

**IATA** 

**UN number** UN3082

**UN proper shipping name** Environmentally hazardous substance, liquid, n.o.s. (DIETHYLTOULENEDIAMINE)

Transport hazard class(es) Class

9 **Subsidiary hazard Packing group** III**Environmental hazards** Yes **ERG Code** 91

Special precautions for

user

Read safety instructions, SDS and emergency procedures before handling.

Other information

Passenger and cargo

aircraft

Allowed with restrictions.

Allowed with restrictions. Cargo aircraft only

**IMDG** 

**UN number** UN3082

**UN proper shipping name** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (DIETHYLTOULENEDIAMINE),

MARINE POLLUTANT

Transport hazard class(es)

9 Class **Subsidiary hazard** Packing group III**Environmental hazards** 

Marine pollutant

Yes F-A, S-F **EmS** 

Special precautions for

user

Read safety instructions, SDS and emergency procedures before handling.


Transport in bulk according to Not established.

Annex II of MARPOL 73/78

and the IBC Code

Material name: FLEXJOINT™ U500 SEALANT PART A RESIN

#### IATA; IMDG



#### Marine pollutant



**General information** IMDG Regulated Marine Pollutant.

## 15. Regulatory information

**US** federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

One or more components of the mixture are not on the TSCA 8(b)

Standard, 29 CFR 1910.1200.

inventory or are designated "inactive". (TSCA)

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

**Toxic Substances Control Act** 

**CERCLA Hazardous Substance List (40 CFR 302.4)** 

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

**SARA 302 Extremely hazardous substance** 

Not listed.

**SARA 311/312** Yes

**Hazardous chemical** 

**Classified hazard** Acute toxicity (any route of exposure) Serious eye damage or eye irritation categories

Respiratory or skin sensitization

SARA 313 (TRI reporting)

Not regulated.

### Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act Not regulated.

(SDWA)

#### **US state regulations**

#### **California Proposition 65**

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins. For more information go to www.P65Warnings.ca.gov.

Material name: FLEXJOINT™ U500 SEALANT PART A RESIN 7853 Version #: 01 Issue date: 02-17-2025

#### **International Inventories**

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Industrial Chemicals (AICIS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes

TaiwanTaiwan Chemical Substance Inventory (TCSI)YesUnited States & Puerto RicoToxic Substances Control Act (TSCA) InventoryYes

## 16. Other information, including date of preparation or last revision

**Issue date** 02-17-2025

Version # 01

NFPA ratings Health: 1

Flammability: 1 Instability: 0

**Disclaimer** Ergon Armor cannot anticipate all conditions under which this information and its product, or

the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.

Material name: FLEXJOINT™ U500 SEALANT PART A RESIN

7853 Version #: 01 Issue date: 02-17-2025 7 / 7

<sup>\*</sup>A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).