

1. Identification**Product identifier** PENNPRIME™ 101**Other means of identification** None.**Recommended use** Not available.**Recommended restrictions** None known.**Manufacturer/Importer/Supplier/Distributor information****Company Name** ErgonArmor, a division of Ergon Asphalt & Emulsions, Inc.**Address** 2829 Lakeland Drive

Jackson, MS 39232

USA

After hours telephone number 1-800-222-7122**Normal work hours telephone number** 1-877-982-7667**Website** www.ergonarmor.com**E-mail** sds@ergon.com**Emergency 24-hour telephone number** CHEMTREC: North America 1-800-424-9300 International 1-800-527-3887**Information on operation hours** 8:00 a.m. to 5:00 p.m.**2. Hazard(s) identification**

Physical hazards	Flammable liquids	Category 3
Health hazards	Skin corrosion/irritation	Category 2
	Serious eye damage/eye irritation	Category 2
	Germ cell mutagenicity	Category 1
	Carcinogenicity	Category 1
	Specific target organ toxicity, single exposure	Category 3 narcotic effects
	Specific target organ toxicity, repeated exposure	Category 2
Environmental hazards	Not classified.	
OSHA defined hazards	Not classified.	

Label elements**Signal word** Danger**Hazard statement** Flammable liquid and vapor. Causes skin irritation. Causes serious eye irritation. May cause genetic defects. May cause cancer. May cause drowsiness or dizziness. May cause damage to organs through prolonged or repeated exposure.**Precautionary statement
Prevention**

Obtain special instructions before use. Wear protective gloves/protective clothing/eye protection/face protection. Do not handle until all safety precautions have been read and understood. Keep container tightly closed. Avoid breathing dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use explosion-proof electrical/ventilating/lighting equipment. Take precautionary measures against static discharge. Use only non-sparking tools. Ground/bond container and receiving equipment. Use only outdoors or in a well-ventilated area.

Response	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation occurs: Get medical advice/attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. Specific treatment see Section 4 of this SDS. If exposed or concerned: Get medical advice/attention. In case of fire: Use appropriate media to extinguish.
Storage	Store locked up. Keep container tightly closed. Store in a well-ventilated place. Keep cool.
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.
Hazard(s) not otherwise classified (HNOC)	None known.
Supplemental information	None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
ASPHALT, OXIDIZED		64742-93-4	50 - 55
MINERAL SPIRITS		8052-41-3/64742-48-9	45 - 50

4. First-aid measures

Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison center or doctor/physician if you feel unwell.
Skin contact	For hot product, immediately immerse in or flush the affected area with large amounts of cold water to dissipate heat. If clothing sticks to the skin, do not remove. Take off immediately all contaminated clothing. Wash contaminated clothing before reuse. Get medical attention immediately.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
Ingestion	Rinse mouth thoroughly. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Call a physician or poison control center immediately.
Most important symptoms/effects, acute and delayed	May cause skin dryness or cracking. Skin irritation. Causes serious eye irritation. Symptoms of overexposure can include shortness of breath, drowsiness, headaches, confusion, decreased coordination, visual disturbances and vomiting, and are reversible if exposure is stopped. Shortness of breath. Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea. May cause redness and pain. Dizziness. Unconsciousness. May cause mild irritation including stinging, watering, and redness.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. If you feel unwell, seek medical advice (show the label where possible). Show this safety data sheet to the doctor in attendance.

5. Fire-fighting measures

Suitable extinguishing media	Water fog. Alcohol resistant foam. Dry chemical powder. Carbon dioxide (CO2).
Unsuitable extinguishing media	Water. Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
Fire fighting equipment/instructions	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk. In the event of fire, cool tanks with water spray.

Specific methods Use standard firefighting procedures and consider the hazards of other involved materials. Move container from fire area if it can be done without risk. Self-contained breathing apparatus and full protective clothing must be worn in case of fire. In the event of fire and/or explosion do not breathe fumes.

General fire hazards Flammable liquid and vapor.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist/vapors. Do not touch or walk through spilled material. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools. The product is immiscible with water and will spread on the water surface. Prevent entry into waterways, sewer, basements or confined areas.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS.

Environmental precautions Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Avoid breathing dust/fume/gas/mist/vapors/spray. Avoid contact with eyes, skin, and clothing. Do not get this material on clothing. Avoid prolonged exposure. Should be handled in closed systems, if possible. Wear appropriate personal protective equipment. Wash thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities Store locked up. Keep away from heat and sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

US. OSHA Table Z-1 Permissible Exposure Limits (PEL) for Air Contaminants (29 CFR 1910.1000)

Material	Type	Value
BLACKHAWK™ 5103 SP ASPHALT PRIMER	PEL	2900 mg/m3
		500 ppm

US. ACGIH Threshold Limit Values (TLV)

Material	Type	Value
BLACKHAWK™ 5103 SP ASPHALT PRIMER	TWA	100 ppm

U.S. - NIOSH**Components**

	Type	Value
ASPHALT, OXIDIZED (CAS 64742-93-4)	REL	5 mg/m3

US. NIOSH: Pocket Guide to Chemical Hazards Recommended Exposure Limits (REL)

Material	Type	Value
BLACKHAWK™ 5103 SP ASPHALT PRIMER	Ceiling	1800 mg/m3
	TWA	350 mg/m3

Biological limit values	No biological exposure limits noted for the ingredient(s).
Appropriate engineering controls	Provide adequate ventilation, including appropriate local extraction, to ensure that the defined occupational exposure limit is not exceeded. Provide eyewash station and safety shower.
Individual protection measures, such as personal protective equipment	
Eye/face protection	Wear safety glasses with side shields (or goggles).
Skin protection	
Hand protection	Chemical resistant gloves are recommended. If contact with forearms is likely wear gauntlet style gloves.
Other	Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.
Respiratory protection	When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.
General hygiene considerations	Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance	Viscous liquid
Physical state	Liquid.
Form	Liquid.
Color	Brown to. Black
Odor	Mild Petroleum Odor
Odor threshold	Not available.
pH	Not available.
Melting point/freezing point	No Data
Initial boiling point and boiling range	300 °F (148.89 °C)
Flash point	> 100.0 - < 140.0 °F (> 37.8 - < 60.0 °C) Cleveland Open Cup
Evaporation rate	Not available.
Flammability (solid, gas)	Not available.
Upper/lower flammability or explosive limits	
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	Not available.
Vapor density	Not available.
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Insoluble
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	No Data
Decomposition temperature	Not available.

Viscosity Not available.

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous reactions Hazardous polymerization does not occur.

Conditions to avoid Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.

Incompatible materials Strong oxidizing agents.

Hazardous decomposition products No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea.

Skin contact Causes skin irritation.

Eye contact Causes serious eye irritation.

Ingestion May cause discomfort if swallowed. However, ingestion is not likely to be a primary route of occupational exposure.

Symptoms related to the physical, chemical and toxicological characteristics Skin irritation. Repeated exposure may cause skin dryness and cracking. Causes serious eye irritation. Irritation to respiratory system. May cause drowsiness or dizziness. Symptoms of overexposure can include shortness of breath, drowsiness, headaches, confusion, decreased coordination, visual disturbances and vomiting, and are reversible if exposure is stopped. Nausea, vomiting. Unconsciousness. May cause redness and pain.

Information on toxicological effects

Acute toxicity

Product	Species	Test Results
PENNPRIME™ 101		
Acute		
Oral		
LD50	Rat	330600 mg/kg

* Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye irritation May be irritating to eyes.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization None known.

Germ cell mutagenicity May cause genetic defects.

Carcinogenicity May cause cancer.

IARC Monographs. Overall Evaluation of Carcinogenicity

ASPHALT, OXIDIZED (CAS 64742-93-4) 2A Probably carcinogenic to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

Reproductive toxicity Not available.

Specific target organ toxicity - single exposure May cause drowsiness or dizziness.

Specific target organ toxicity - repeated exposure May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard Not available.

Further information Symptoms may be delayed.

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Product		Species	Test Results
PENNPRIME™ 101			
Aquatic			
Crustacea	EC50	Daphnia	2939.8572 mg/l, 48 hours
Fish	LC50	Fish	12194.8398 mg/l, 96 hours

* Estimates for product may be based on additional component data not shown.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions Dispose of this material and its container to hazardous or special waste collection point. Incinerate the material under controlled conditions in an approved incinerator. Do not incinerate sealed containers. Do not allow this material to drain into sewers/water supplies. If discarded, this product is considered a RCRA ignitable waste, D001. Dispose of contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code D001: Waste Flammable material with a flash point <140 F
The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

Waste from residues / unused products Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT

UN number	UN1999
UN proper shipping name	Tars, liquid including road oils and cut back bitumens
Transport hazard class(es)	
Class	3
Subsidiary hazard	-
Label(s)	3
Packing group	III
Environmental hazards	
Marine pollutant	No.
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling. If shipped by ground in individual containers that are less than 119 gallons (450 L): Not regulated as a hazardous material. (49 CFR 173.121)
Special provisions	B1, B13, IB3, T1, TP3
Packaging exceptions	150
Packaging non bulk	203
Packaging bulk	242

IATA

UN number	UN1999
UN proper shipping name	Tars, liquid including road asphalt and oils, bitumen and cut backs
Transport hazard class(es)	
Class	3
Subsidiary hazard	-

Packing group III
Environmental hazards No.
ERG Code 3L
Special precautions for user Read safety instructions, SDS and emergency procedures before handling.
Other information
Passenger and cargo aircraft Allowed with restrictions.
Cargo aircraft only Allowed with restrictions.

IMDG

UN number UN1999
UN proper shipping name TAR, LIQUID including road oils, and cutback bitumens
Transport hazard class(es)
Class 3
Subsidiary hazard -
Packing group III
Environmental hazards
Marine pollutant No.
EmS F-E, S-E
Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not established.

DOT



IATA; IMDG



General information

If shipped by ground in individual containers that are less than 119 gallons (450 L): Not regulated as a hazardous material (49 CFR 173.121). If shipped by vessel in individual containers that are less than 119 gallons (450 L) each, then IMDG 2.3.2.5 exception applies. Not subject to the provisions for marking, labelling, and testing of packages. "Transport in accordance with 2.3.2.5 of the IMDG code."

15. Regulatory information

US federal regulations

All components are on the U.S. EPA TSCA Inventory List. This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

Toxic Substances Control Act (TSCA)

All components of the mixture on the TSCA 8(b) inventory are designated "active".

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)**SARA 302 Extremely hazardous substance**

Not listed.

SARA 311/312

Yes

Hazardous chemical**Classified hazard categories**

Skin corrosion or irritation
 Serious eye damage or eye irritation
 Germ cell mutagenicity
 Carcinogenicity
 Specific target organ toxicity (single or repeated exposure)

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations**Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List**

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA) Not regulated.**US state regulations****California Proposition 65**

WARNING: WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

California Proposition 65 - CRT: Listed date/Carcinogenic substance

ASPHALT, OXIDIZED (CAS 64742-93-4)

Listed: January 1, 1990

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Industrial Chemicals (AICIS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision**Issue date** 03-18-2025**Version #** 01

Further information

HMIS® is a registered trade and service mark of the NPCA.

NFPA ratings

Health: 2
Flammability: 2
Instability: 0

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. Ergon Armor cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.

Revision information

Product and Company Identification: Alternate Trade Names
Hazard(s) identification: Hazard(s) not otherwise classified (HNOC)
Hazard(s) identification: GHS Symbols
Physical & Chemical Properties: Multiple Properties
Stability and reactivity: Possibility of hazardous reactions
Stability and reactivity: Chemical stability
Toxicological information: Chronic effects
Transport Information: Proper Shipping Name/Packing Group
GHS: Classification